


Radial Electrolytic Capacitors (continued)

ELRA-SK Series



STANDARD / 85°


Miniature aluminium electrolytic capacitors with radial leads for general purposes.

Technical parameters	ELRA-SK
Capacitance	0.47uF-4700uF
Rated voltage	16-450V DC
Operating temp. range	-40°C ... +85°C
Operational life	2000 hours/85°C
Manufacturer's marking	SKR
Ordering code	ELRA 10uF 35V SK

Capacitance	Ord.No.	P[mm]	DxL [mm]
16V			
S 220 uF	49257	2,5	6,3x11
S 330 uF	15742	3,5	8x11
S 470 uF	15743	3,5	8x11
S 2200 uF	15745	5,1	13x26
S 3300 uF	15746	5	13x26
S 4700 uF	22974	7,5	16x25
25V			
S 47 uF	49479	2	5x11
S 100 uF	39820	2,5	6,3x11
S 220 uF	15748	3,5	8x11
S 470 uF	15749	5	10x13
S 1000 uF	15750	5	10x21
S 2200 uF	21941	5	13x26
S 4700 uF	36204	7,5	18x35
35V			
S 33 uF	15754	2	5x11
S 100 uF	15756	2,5	6,3x11
S 220 uF	49259	3,5	8x11
S 330 uF	15758	5	10x13
S 470 uF	15759	5	10x16
S 1000 uF	15762	5	13x21
S 2200 uF	15764	7,5	16x25
S 3300 uF	15766	7,5	16x35
S 4700 uF	22975	7,5	18x35
50V			
S 100 uF	26212	3,5	8x11
S 220 uF	26213	5	10x13
S 470 uF	26214	5	13x21
S 1000 uF	26215	5	13x26
S 2200 uF	36217	7,5	18x35
63V			
S 10 uF	15773	2	5x11
S 22 uF	15774	2	5x11
S 47 uF	15776	2,5	6,3x11
S 100 uF	15777	5	10x13
S 220 uF	15778	5	10x16
S 470 uF	15780	5	13x21
S 1000 uF	20335	7,5	16x25
100V			
S 0,47 uF	15781	2	5x11
S 1 uF	15782	2	5x11
S 2,2 uF	26216	2	5x11
S 4,7 uF	26217	2	5x11
S 10 uF	26218	2,5	6,3x11
S 22 uF	26219	2,5	6,3x11
S 47 uF	26220	5	10x17
S 100 uF	26221	5	13x21
200V			
S 10 uF	25227	5	10x16

Capacitance	Ord.No.	P[mm]	DxL [mm]
400V			
4,7 uF	25230	5	10x20
10 uF	25231	5	12,5x20
450V			
4,7 uF	40280	5	10x18
10 uF	40281	5	13x21
22 uF	40722	7,5	16x25

E105-TK Series



STANDARD / 105°

Miniature aluminium electrolytic capacitors with radial leads for general purposes. Wide temperature range.

Technical parameters	E105-TK
Capacitance	1uF-4700uF
Rated voltage	16-450V DC
Operating temp. range	-40°C ... +105°C
Operational life	2000 hours/85°C
Manufacturer's marking	TKR (bulk), TKP (reel)
Ordering code	E105 47uF 25V TK

Capacitance	Ord.No.	P[mm]	DxL [mm]
16V			
S 1000 uF	60813	5	10x16
S 4700 uF	49508	3,5	8x12
25V			
S 47 uF	48590	2	5x11
S 100 uF	39708	2,5	6x12
S 1000 uF	49701	5	10x20
50V			
S 22 uF	49702	2	5x11
S 47uF	39729	5	6,3x11
S 100 uF	49500	3,5	8x12
S 220 uF	39731	5	10x16
S 470 uF	39733	5	10x20
S 1000 uF	39734	5	12,5x25
S 2200 uF	53371	7,5	16x35,5
63V			
S 4,7uF	39744	5	5x11
S 10 uF	49497	2	5x11
S 22 uF	39746	5	6x11
S 1000 uF	39753	7,5	16x25
100V			
S 1 uF	39741	2	5x11
S 2,2 uF	39742	2	5x11
S 220 uF	48635	5	12,5x25
S 470 uF	39769	7,5	16x25
450V			
S 1uF	53179	5	10x12,5
S 2,2 uF	53180	5	10x20
S 4,7uF	53181	5	12,2x20