

2J020 Series



Part No.	2J030
Frequency	AMPS 824-894MHz / GSM 900 MHz / UMTS 2.1 GHz / WIFI / BLUETOOTH 2.4 GHz / PCN 1800 MHz / DCS 1900 MHz
Impedance	50 Ohms
Polarization	VERTICAL
Gain	2.2 dBi
VSWR	<2:1
Connector	SMA Male
Housing size	55mm x 9.65mm

Part No.	Ord.No.
S 2J020 (black)	54955
S 2J020W (white)	68025

2J030 Series



Part No.	2J030
Frequency	AMPS 824-894MHz / GSM 900 MHz / UMTS 2.1 GHz / WIFI / BLUETOOTH 2.4 GHz / PCN 1800 MHz
Impedance	50 Ohms
Polarization	VERTICAL
Gain	2.2 dBi
VSWR	<2:1
Connector	FME Female
Housing size	61mm x 9.65mm

Part No.	Ord.No.
S 2J030	68026
S 2J030W (white)	78254

2J040 Series



Part No.	2J040
Frequency	AMPS 824-894MHz / GSM 900 MHz / UMTS 2.1 GHz / WIFI / BLUETOOTH 2.4 GHz / PCN 1800 MHz / DCS 1900 MHz
Impedance	50 Ohms
Polarization	VERTICAL
Gain	2.2 dBi
VSWR	<2:1
Connector	FME Female 90°
Housing size	53mm x 9.65mm

Part No.	Ord.No.
S 2J040	68027

2J050 Series



Part No.	2J030
Frequency	AMPS 824-894MHz / GSM 900 MHz / UMTS 2.1 GHz / WIFI / BLUETOOTH 2.4 GHz / PCN 1800 MHz / DCS 1900 MHz
Impedance	50 Ohms
Polarization	VERTICAL
Gain	2.2 dBi
VSWR	<2:1
Connector	SMA Male
Housing size	54mm x 9.65mm

Part No.	Ord.No.
S 2J050	68028

2JW04 Series



Part No.	2J030
Frequency	GSM 900 MHz / PCN 1800 MHz
Impedance	50 Ohms
Polarization	VERTICAL
Gain	2.2dB at 900MHz
VSWR	<2:1
Connector	FME Female
Housing size	146mm x 10mm dia.

Part No.	Ord.No.
S 2J320M	78260
S 2J320M MFE	78263

2J GPS Combined Antennas

2J860B - "Shark" GPS/Glonass/GSM/WIFI Antenna



Part No.	2J860B
Frequency	GLONASS 1572MHz to 1610MHz / AMPS/GSM/WIFI/ GPS / GPS 1575.42 MHz
Impedance	50 Ohm
Mounting	any surface
Polarization	GPS RHCP , GSM vertical
Gain	GPS 26 - 28 dBi , GSM 3dBi max.
VSWR	<2:1 for GSM <1,2:1 for GPS
Voltage supply	2,7V to 5,5V
Current	15mA-25mA
Power (max.)	138mW
Cable	RG 174 5m/5m
Connector	SMA/SMA
Housing size	91 mm x 52 mm x 48 mm

Part No.	Ord.No.
S 2J860B	71466

2J600 Series

2J600B

2J600M



Part No.	2J600B	2J600M
Frequency	AMPS 824-894MHz / GSM 900 MHz / UMTS 2.1 GHz / PCN 1800 MHz / GPS 1575.42 MHz	
Impedance	50Ohms	
Mounting	Body Mount	Magnetic mount
Polarization	RHCP	
Gain	0 dBi	
VSWR	<2:1	
Power handling	50W	
Voltage supply	3V - 5V	
Current	15mA - 25mA	
Power (max.)	125mW	
Cable	RG174 2,5m	
Connector	GSM: FME Female, GPS: SMB Female	
Housing size	80mm x 75mm	

Part No.	Ord.No.
S 2J600B	66264
S 2J600M	66263