

Accessories

SPS-1

Universal safety rest with sponge.



Part No.	Ord.No.
S SPS-1	1768
S ST-51	45903

ST-51

Solder Reel Holder. Maximum 500g., width 70mm. Guide spring to avoid solder tangle.



NRU-0083 (0100)

Vacuum SMD tool kit for ESD-protected work

Consist of:

- vacuum tweezer,
- 4pcs replaceable tips
- Length 70mm
- Diameter 13mm

Part No.	Ord.No.
S NRU-0083	52272

VAC X

Antistatic, Standard Solder Sucker (desoldering tool) with teflon nozzle, 11.3cm suction capacity.



VAC X2/SB

Replacement desoldering teflon nozzle for VAC X



Part No.	Ord.No.
S VAC X	48333
S VAC X2/SB	48334

NS 098

Standard Solder Sucker (desoldering tool) with teflon nozzle.



SH813

Standard Solder Sucker (desoldering tool) with teflon nozzle.



Part No.	Ord.No.
S NS 098	26385
S SH813	48384



TIP NS 098 SPITZE

Replacement teflon nozzle for NS 098.

Part No.	Ord.No.
S Tip- NS 098	26386



AMASAN

Solder Sucking Wick

Flexible cooper braid designed for desoldering
Impregnated with synthetic flux

Part No.	Ord.No.	Width / Length
S AMASAN 2	30078	1,5mm / 1,6m
S AMASAN 3	30079	2,0mm / 1,6m
S AMASAN 4	30080	2,5mm / 1,6m
S AMASAN 5	62259	2,5mm / 1,5m

Fume Extractors

Weller®

The WFE is a fume extraction unit suitable for applications with a high demand for gas and particle filtration, e.g. soldering, adhesives, clean room work and laser. It can be placed on a trolley and be moved easily between different work places. Variable speed and the alarm function for filter exchange can be set also via the remote control. For applications which produce a large quantity of particles, e.g. lead-free soldering, an external pre-filter can be fitted to increase the lifetime of the main filter. To make cleaning easier, the WFE can be suspended under the work table with special fittings.

WFE 2S



WFE 4S



Technical Parameters	WFE 2S	WFE 4S
Electrical Power	275VA	450VA
Power Supply	230V / 50Hz	230V / 50Hz
Max. pressure	2700 Pa	2800 Pa
Max. airflow	230 m3/h	615 m3/h
Max. capacity	3 work places	8 work places
Weight	19kg	21kg
Dimensions L x W x H	320mm x 320mm x 395mm	450mm x 450mm x 650mm

Part No.	Ord.No.
o WFE 2S	70568
o WFE 4S	63669

WFAF 50

Fume Extraction Arm With Nozzle End, l=1000mm d=100mm.



WFAN 50

Fume Extraction Arm With Round Funnel End, l=800mm.



WFAS 50

Fume Extraction Arm With Flat Nozzle End, l=1000mm 210x20mm.



Part No.	Ord.No.
o WFAF 50	67580
o WFAN 50	63672
o WFAS 50	66281

005 36 321 99

Branch, 2 x 45°, 1 m, with 2 seals, d=50mm plastic, black.



WE 87 353 27

Extraction hose d=50mm, plastic



WE 87 358 47


Hose connection for Extraction hose d=50mm plastic.



Part No.	Ord.No.
o WE 536 321 99	64352
o WE 587 353 27	63670
o WE 587 358 47	63671

WFE 4S FILTER

HEPA filter, 50% active carbon, 50% Puratex)



WFFMP 50

Seal d=50mm.



WFTB 50

Bench mounting bracket for WFFMP 50.



Part No.	Ord.No.
o WFE 4S FILTER	66260
o WFFMP 50	63673
o WFTB 50	63674